


Fast HF measurements.
Anywhere.

NEW



Hydrogen Fluoride Analyzer (HF, H₂O)

Features and Benefits

- Fastest response: 1-Hz measurements: allow observation of transient and time varying flows
- Measures a wide range of concentrations
- High-resolution absorption spectra always viewable
- Low power: ideal for field applications
- New Enhanced Performance model provides ultra-low drift and unsurpassed precision

LGR's Hydrogen Fluoride Analyzer (HFA) provides sensitive measurements of HF in ambient air or in industrial process flows with extremely high precision and sensitivity. No longer do you have to spend a lot of money or wait a long time to measure hydrogen fluoride gas with high sensitivity – LGR's Hydrogen Fluoride Analyzer provides measurements every second with ppb-level precision. In addition, the HFA can report measurements quickly over a very wide range of HF concentrations.

LGR's HFA is available in different packages to allow users to select the one most suitable for their needs. LGR's standard LGR's rackmount package fits in a standard instrumentation rack and requires an external keyboard, mouse, and video monitor. For highest performance, the HF Analyzer is now available in LGR's "Enhanced Performance" (or EP) package. The EP version incorporates proprietary internal thermal control for ultra-stable measurements with unsurpassed precision, accuracy and drift. In addition, the HFA is now available in LGR's "ultraportable" package which is compact, crushproof and is small enough to be carried on-board aircraft (TSA approved).

LGR's analyzers provide reliable *guaranteed* measurements at mole fractions more than 20 times ambient levels. In addition, a suite of options and accessories expands the usability for just about any application.

The HFA uses LGR's patented Off-axis ICOS technology, a fourth-generation cavity enhanced absorption technique. Off-axis ICOS has many advantages over conventional cavity ringdown spectroscopy (CRDS) techniques such as being alignment insensitive, having a much shorter measurement time, and not requiring expensive and power consuming auxiliary components.

As with all LGR instruments, the HFA includes an internal computer (Linux OS) that can store data practically indefinitely on its internal hard drive (for long-term operation), and that can send real-time data to a data logger through its analog, digital and Ethernet outputs. Furthermore, the HFA may be controlled remotely via the Internet. This capability allows the user to easily and fully control the analyzer simply using a web browser.

Hydrogen Fluoride Analyzer (HF, H₂O)

Performance Specifications

Precision (1 σ , 1 sec / 100 sec):

1 ppbv / 0.1 ppb

Maximum Drift (Enhanced Performance model) (15 min average, at STP, over 24 hrs):

0.1 ppb

Detection limit:

0.1 ppb

Measurement Range (meets specs):

0.1 – 2000 ppb

Operational Range

(external calibration may be required):

0 – 30 ppm

Measurement Rates (user selectable):

0.01 – 1 Hz

(external pump required for <10 second flow response)

Sampling Conditions:

Sample Temperature: 0 – 50 °C

Operating Temperature: 0 – 45 °C

Ambient Humidity: 0-100% RH non-condensing

Outputs:

Digital (RS232), analog, Ethernet, USB

Power Requirements:

115/230 VAC, 50/60 Hz or 12 VDC

Standard model: 100 watts

Enhanced Performance model: 150 watts (steady state)

Ultraportable: 70 watts

Dimensions:

Standard model: 8.75" x 19" x 24"

Enhanced Performance model: 14" x 19" x 24"

Ultraportable: 18.5" x 14" x 7"

Weight:

29 kg (Standard model)

40 kg (Enhanced Performance model)

19 kg (Ultraportable)



Ordering Information

907-0017: Standard (rackmount)

911-0017: Enhanced Performance (rackmount)

915-0017: Ultraportable

Accessories

908-0003-9001: Multiport Inlet Unit –
Automated control of up to 16 inlet ports

908-0003-9002: Multiport Inlet Unit –
Automated control of up to 8 inlet ports

908-0001-9011: N920 Pump –
Flow-through time = 1.2 seconds (note that the standard
internal pump provides < 8 seconds 1/e flow response time)

904-0002: Data Logging System – multi-channel data logging
system records and synchronizes serial (RS-232) outputs from
multiple LGR analyzers and other devices (GPS, anemometers)